





































































142	DS-2DE4425IW-DE T5	4MP 25× Network IR Speed Dome - 1/2.8" progressive scan CMOS Up to 2560 × 1440@30fps resolution-Min. illumination: Color: 0.005 Lux @(F1.6, AGC ON) B/W: 0.001 Lux @(F1.6, AGC ON) 0 Lux with IR 25× optical zoom Focal Length 4.8 mm to 120 mm - 16× digital zoom - WDR, HLC, BLC, 3D DNR, Defog, EIS, Regional Exposure, Regional Focus - Up to 100 m IR distance - 12 VDC & PoE+ (802.3 at, class4) Support H.265+/H.265 video compression - Excellent low-light performance with powered-by-DarkFighter technology	IRR 228,010,000	
143	DS-2DE5432IW-AE-S5	5-inch 4 MP 32X Powered by DarkFighter IR Network Speed Dome 1/2.8" Progressive Scan CMOS High quality imaging with 4 MP resolution Excellent low-light performance with powered-by-DarkFighter technology 32× optical zoom, 16× digital zoom WDR, HLC, BLC, 3D DNR, Defog, Regional Exposure, Regional Focus, Rapid Focus Up to 150 m IR distance Accurate human and vehicle target classification, alarm, and linked tracking based on deep learning algorithm Face capture: Up to 5 faces captured at the same time	تماس بگیریید	
144	DS-2DE5220IW-AE	DS-2DE5220IW-AE 2MP 20× Network IR Speed Dome 2.54cm(1/2.8") Progressive Scan CMOS Up to 1920 × 1080 resolution 20× Optical Zoom, 16× Digital Zoom Digital WDR 3D intelligent positioning function Up to 150 m IR distance Hi-PoE/24 VAC power supply Support H.265 video compression	تماس بگیریید	
145	DS-2DE4A320IW-DE	3MP Network IR PTZ Camera 1/2.8" Progressive Scan CMOS Up to 2048 × 1536 resolution 20× Optical Zoom, 16× Digital Zoom WDR, 3D DNR, HLC, Smart IR Up to 50 m IR distance 12 VDC & PoE+ (802.3at, class4) Support H.265 video compression	تماس بگیریید	







146	DS-2DF6A236X-AEL	<p>6-inch 2 MP 36X DarkFighter Network Speed Dome  High quality imaging with 2 MP resolution  Excellent low-light performance via DarkFighter technology  36x optical zoom provides close up views over expansive areas  Intelligent functions based on deep learning  Water and dust resistant (IP67) and vandal proof (IK10).</p>	تماس بگیریید	
147	DS-2CD7A232IW-AEB(T5)	<p>7-inch 2MP 32X Powered by DarkFighter IR Network Speed Dome  1/1.8" progressive scan CMOS  High quality imaging with 4 MP resolution  Excellent low-light performance with powered-by-DarkFighter technology  Audio visual alarm: The white flashing light and audible warning can be triggered by certain events  32x optical zoom and 16x digital zoom provide close up views over expansive areas  Expansive night view with up to 200 m IR distance  Focuses on human and vehicle targets classification based on deep learning  Face capture: Up to 5 faces captured at the same time</p>	تماس بگیریید	
148	DS-2DE7A432IW-AEB (T5)	<p>7-inch 4 MP 32X Powered by DarkFighter IR Network Speed Dome  1/1.8" progressive scan CMOS  High quality imaging with 4 MP resolution  Excellent low-light performance with powered-by-DarkFighter technology  Audio visual alarm: The white flashing light and audible warning can be triggered by certain events  32x optical zoom and 16x digital zoom provide close up views over expansive areas  Expansive night view with up to 200 m IR distance  Focuses on human and vehicle targets classification based on deep learning  Face capture: Up to 5 faces captured at the same time</p>	IRR 360,110,000	
155	DS-2DF8236I5W-AELW	<p>High quality imaging with 2 MP resolution  Excellent low-light performance via powered-by-DarkFighter technology  Clear imaging against strong back lighting due to 120 dB WDR technology  Pan and tilt ability enables camera to monitor zones of interest  32x optical zoom allows for closer viewing of subjects in expansive areas  Up to 150m IR range ensures safety at night  Water and dust resistant (IP66).</p>	IRR 1,143,020,000	
158	NVR 4 Channel			
159	DS-7104NI-Q1/M	<p>IP video input : 4-ch Up to 4 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 40 Mbps - HDMI output : 1920 × 1080p/60Hz - Capacity : 1 SATA interface Up to 6TB capacity</p>	تماس بگیریید	






160	DS-7104NI-Q1	<p>4-ch Mini 1U NVR  H.265+/H.265/H.264+/H.264 video compression  Up to 40 Mbps incoming bandwidth, and 60 Mbps outgoing bandwidth  Up to 4-ch network camera inputs  Up to 4-ch 1080p decoding capability  HDMI and VGA simultaneous output</p>	تماس بگیرید	
161	DS-7104NI-Q1/4P/M	<p>IP video input : 4-ch / 4-ch POE Up to 4 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 40 Mbps - HDMI output : 1920 × 1080p/60Hz - Capacity : 1 SATA interface Up to 6TB capacity</p>	تماس بگیرید	
162	DS-7604NI-Q1	<p>IP video input : 4-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 40 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 1 SATA interface Up to 6TB capacity</p>	تماس بگیرید	
163	DS-7604NI-Q1/4P	<p>IP video input : 4-ch / 4-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 40 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 1 SATA interface Up to 6TB capacity</p>	تماس بگیرید	
164	DS-7604NI-K1	<p>IP video input : 4-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 40 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 1 SATA interface Up to 6TB capacity</p>	IRR 51,380,000	
165	DS-7604NI-K1/4P	<p>IP video input : 4-ch - 4-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 40 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 1 SATA interface Up to 6TB capacity</p>	IRR 79,430,000	
166	NVR 8 Channel			
167	DS-7108NI-Q1/M	<p>IP video input :8-ch Up to 4 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 60 Mbps - HDMI output : 1920 × 1080p/60Hz - Capacity : 1 SATA interface Up to 6TB capacity</p>	تماس بگیرید	

168	DS-7108NI-Q1/8P/M	IP video input :8-ch / 8-ch POE Up to 4 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 60 Mbps - HDMI output : 1920 × 1080p/60Hz - Capacity : 1 SATA interface Up to 6TB capacity	تماس بگیریید	
169	DS-7608NI-Q2/8P	IP video input : 8-ch / 8-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 80 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	تماس بگیریید	
170	DS-7608NI-Q1	Up to 8-ch IP camera inputs H.265+/H.265/H.264+/H.264 video formats Up to 1-ch@8 MP/3-ch@4 MP/6-ch@1080p decoding capacity Up to 80 Mbps incoming bandwidth	تماس بگیریید	
171	DS-7608NI-Q2	Up to 8-ch IP camera inputs H.265+/H.265/H.264+/H.264 video formats Up to 1-ch@8 MP/3-ch@4 MP/6-ch@1080p decoding capacity Up to 80 Mbps incoming bandwidth	تماس بگیریید	
172	DS-7608NI-K1	IP video input : 8-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 80 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 1 SATA interface Up to 6TB capacity	IRR 68,340,000	
173	DS-7608NI-K1/8P	8-ch 1U 8 PoE 4K NVR Up to 8-ch IP camera inputs H.265+/H.265/H.264+/H.264 video formats Up to 1-ch@8 MP/3-ch@4 MP/6-ch@1080p decoding capacity Up to 80 Mbps incoming bandwidth	IRR 126,190,000	
174	DS-7608NI-K2	8-ch 1U 4K NVR Up to 8-ch IP camera inputs H.265+/H.265/H.264+/H.264 video formats Up to 2-ch@8 MP or 4-ch@4 MP or 8-ch@1080p decoding capacity 1 HDMI and 1 VGA interfaces, both interfaces support independent video output 2 SATA interfaces for HDD connection (up to 10 TB capacity per HDD) Up to 80 Mbps incoming bandwidth	IRR 71,200,000	
175	NVR 16 Channel			




176	DS-7616NI-Q1	IP video input : 16-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 1 SATA interface Up to 6TB capacity	تماس بگیریید	
177	DS-7616NI-Q2	IP video input : 16-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	IRR 79,080,000	
178	DS-7616NI-Q2/16P	IP video input : 16-ch / 16-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	تماس بگیریید	
179	DS-7616NXI-K1	16-ch 1U K Series AcuSense 4K NVR Up to 16-ch IP camera inputs H.265+/H.265/H.264+/H.264 video formats Up to 2-ch@12 MP or 3-ch@8 MP or 6-ch@4 MP or 12-ch@1080p decoding capacity Up to 160 Mbps incoming bandwidth	IRR 82,240,000	
180	DS-7616NXI-K2	16-ch 1U K Series AcuSense 4K NVR Up to 16-ch IP camera inputs H.265+/H.265/H.264+/H.264 video formats Up to 2-ch@12 MP or 3-ch@8 MP or 6-ch@4 MP or 12-ch@1080p decoding capacity Up to 160 Mbps incoming bandwidth	IRR 83,420,000	
181	DS-7616NXI-K2/16P	16-ch PoE 1U K Series AcuSense 4K NVR Up to 16-ch IP camera inputs, plug & play with 16 Power-over-Ethernet (PoE) interfaces H.265+/H.265/H.264+/H.264 video formats Up to 2-ch@12 MP or 3-ch@8 MP or 6-ch@4 MP or 12-ch@1080p decoding capacity Up to 160 Mbps incoming bandwidth Adopt Hikvision Acusense technology to minimize manual effort and security costs	IRR 203,190,000	
182	DS-7616NI-K1	Up to 16-ch IP camera inputs H.265+/H.265/H.264+/H.264 video formats Up to 1-ch @ 8MP or 5-ch @ 1080P decoding capacity Up to 160 Mbps incoming bandwidth	تماس بگیریید	

183	DS-7616NI-K2	IP video input : 16-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	تماس بگیریید	
184	DS-7616NI-K2/16P	IP video input : 16-ch / 16-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	IRR 203,190,000	
185	DS-7716NI-Q4	IP video input : 16-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	IRR 178,100,000	
186	DS-7716NI-Q4/16P	IP video input : 16-ch / 16-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	IRR 255,140,000	
187	DS-7716NI-K4	IP video input : 16-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	IRR 189,980,000	
188	DS-7716NXI-K4	16-ch 1.5U K Series AcuSense 4K NVR Up to 16-ch IP camera inputs H.265+/H.265/H.264+/H.264 video formats Up to 2-ch@12 MP or 3-ch@8 MP or 6-ch@4 MP or 12-ch@1080p decoding capacity Up to 160 Mbps incoming bandwidth Adopt Hikvision Acusense technology to minimize manual effort and security costs	IRR 205,510,000	


189	DS-7716NI-K4/16P	IP video input : 16-ch / 16-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	تماس بگیریید	
190	Network Video Recorders- Ultra Series			
191	DS-8616NI-K8	16-ch 2U 4K NVR,Up to 16 channel IP cameras can be connected,Supports decoding H.265+/H.265/H.264+/H.264/MPEG4 video formats Up to 4K high-definition live view, storage and playback, Up to 160 Mbps high incoming bandwidth ensures IP cameras can be connected,2 HDMI (different source) and 2 VGA (different source) interfaces,8 HDD can be used for continuous video recording,Supports some specialist cameras, including people counting camera/ANPR (automatic number plate recognition) camera	IRR 147,000,000	
192	NVR 32 Channel			
193	DS-7732NI-Q4	IP video input : 32-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 200 Mbps - HDMI output : 1920 × 1080/60Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	تماس بگیریید	
194	DS-7732NI-Q4/16P	IP video input : 32-ch / 16-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 200 Mbps - HDMI output : 1920 × 1080/60Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	IRR 203,190,000	
195	DS-7732NI-K4	IP video input : 32-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 256 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	IRR 226,950,000	
196	DS-7732NXI-K4	32-ch 1.5U K Series AcuSense 4K NVR Up to 32-ch IP camera inputs H.265+/H.265/H.264+/H.264 video formats Up to 2-ch@12 MP or 3-ch@8 MP or 6-ch@4 MP or 12-ch@1080p decoding capacity Up to 256 Mbps incoming bandwidth Adopt Hikvision Acusense technology to minimize manual effort and security costs	IRR 226,950,000	

197	DS-7732NXI-I4/S	<p>32-ch 1.5U K Series AcuSense 4K NVR  Up to 32-ch IP camera inputs  H.265+/H.265/H.264+/H.264 video formats  Up to 2-ch@12 MP or 3-ch@8 MP or 6-ch@4 MP or 12-ch@1080p decoding capacity  Up to 256 Mbps incoming bandwidth  Adopt Hikvision Acusense technology to minimize manual effort and security costs</p>	IRR 383,950,000	
198	IDS-7732NXI-I4/8S	<p>32-ch 1.5U 4K DeepinMind NVR  H.265+/H.265/H.264+/H.264 video formats  Intelligent analytics based on deep learning algorithm  Up to 16-ch perimeter protection  Up to 8-ch facial recognition for video stream, or up to 16-ch facial recognition for face picture  Up to 8-ch video structuralization  Up to 32-ch IP cameras can be connected  Up to 16-ch 1080p decoding capability</p>	IRR 719,160,000	
199	DS-7732NI-K4/16P	<p>IP video input : 32-ch - 16-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 -  Incoming bandwidth : 256 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 4 SATA interface Up to 6TB  capacity for each disk</p>	IRR 320,940,000	
200	DS-8632NI-K8	<p>Up to 32 channel IP cameras can be connected  Supports decoding H.265+/H.265/H.264+/H.264/MPEG4 video formats  Up to 4K high-definition live view, storage and playback  Up to 160 Mbps high incoming bandwidth ensures IP cameras can be connected  2 HDMI (different source) and 2 VGA (different source) interfaces  8 HDD can be used for continuous video recording  Supports some specialist cameras, including people counting camera/ANPR (automatic number plate  recognition) camera</p>	IRR 218,820,000	
201	IDS-9632NXI-I8/4F	<p>32-ch 2U 4K DeepinMind NVR  H.265+/H.265/H.264+/H.264 video formats  Up to 32 channel IP cameras can be connected  8 HDD can be used for continuous video recording  Intelligent analytics based on deep learning algorithm  Up to 16-ch perimeter protection  Up to 8-ch facial recognition for video stream, or up to 16-ch facial recognition for face picture  Up to 4-ch video structuralization  Up to 16-ch 1080p decoding capability</p>	IRR 3,213,890,000	



202	DS-9632NXI-I8/S	<p>32-ch 2U 4K AcuSense NVR  H.265+/H.265/H.264+/H.264 video formats  Intelligent analytics based on deep learning algorithm  Up to 4-ch perimeter protection  Up to 1-ch facial recognition for video stream, or up to 4-ch facial recognition for face picture  Up to 32-ch IP camera inputs  Up to 16-ch 1080p decoding capability  Up to 320 Mbps incoming bandwidth</p>	تماس بگیریید	
203	DS-9632NI-I8	<p>32-ch 2U 4K NVR  Up to 32 channel IP cameras can be connected  Up to 12 MP high-definition live view, storage and playback  Up to 320 Mbps (or 200 Mbps when RAID is enabled) high incoming bandwidth ensures IP cameras can be connected  2 HDMI (different source) and 2 VGA (different source) interfaces  8 HDD can be used for continuous video recording  Supports some specialist cameras, including people counting camera/ANPR (automatic number plate recognition) camera/fisheye camera  Advanced streaming technology enables smooth live view in poor network conditions  Supports RAID 0, 1, 5, 6, 10 and N+1 hot spare for even more reliable data storage, effectively avoids data loss risks</p>	تماس بگیریید	
204	DS-9632NI-I16	<p>32-ch 3U 4K NVR  Up to 32 channel IP cameras can be connected  Up to 320 Mbps (or 200 Mbps when RAID is enabled) high incoming bandwidth ensures IP cameras can be connected  2 HDMI (different source) and 2 VGA (different source) interfaces  16 HDD can be used for continuous video recording  Supports some specialist cameras, including people counting camera/ANPR (automatic number plate recognition) camera/fisheye camera  Advanced streaming technology enables smooth live view in poor network conditions  Supports RAID 0, 1, 5, 6, 10 and N+1 hot spare for even more reliable data storage, effectively avoids data loss risks</p>	تماس بگیریید	

205	DS-9664NI-I8	<p>64-ch 2U 4K NVR</p> <p>Up to 64 channel IP cameras can be connected</p> <p>Up to 12 MP high-definition live view, storage and playback</p> <p>Up to 320 Mbps (or 200 Mbps when RAID is enabled) high incoming bandwidth ensures IP cameras can be connected</p> <p>2 HDMI (different source) and 2 VGA (different source) interfaces</p> <p>8 HDD can be used for continuous video recording</p> <p>Supports some specialist cameras, including people counting camera/ANPR (automatic number plate recognition) camera/fisheye camera</p> <p>Advanced streaming technology enables smooth live view in poor network conditions</p> <p>Supports RAID 0, 1, 5, 6, 10 and N+1 hot spare for even more reliable data storage, effectively avoids data loss risks</p>	تماس بگیریید	
206	DS-9664NXI-I8/S	<p>64-ch 2U 4K AcuSense NVR</p> <p>H.265+/H.265/H.264+/H.264 video formats</p> <p>Intelligent analytics based on deep learning algorithm</p> <p>Up to 4-ch perimeter protection</p> <p>Up to 1-ch facial recognition for video stream, or up to 4-ch facial recognition for face picture</p> <p>Up to 64-ch IP camera inputs</p> <p>Up to 16-ch 1080p decoding capability</p> <p>Up to 320 Mbps incoming bandwidth</p>	تماس بگیریید	
207	DS-8664NI-I8	<p>64-ch 2U 4K NVR</p> <p>Up to 64 channel IP cameras can be connected</p> <p>Up to 12 MP high-definition live view, storage and playback</p> <p>Up to 320 Mbps (or 200 Mbps when RAID is enabled) high incoming bandwidth ensures IP cameras can be connected</p> <p>2 HDMI (different source) and 2 VGA (different source) interfaces</p> <p>8 HDD can be used for continuous video recording</p> <p>Supports some specialist cameras, including people counting camera/ANPR (automatic number plate recognition) camera/fisheye camera</p> <p>Advanced streaming technology enables smooth live view in poor network conditions</p> <p>Supports RAID 0, 1, 5, 6, 10 and N+1 hot spare for even more reliable data storage, effectively avoids data loss risks</p>	تماس بگیریید	
208	DS-9664NI-I16	<p>64-ch 3U 4K NVR</p> <p>Up to 64 channel IP cameras can be connected</p> <p>Up to 320 Mbps (or 200 Mbps when RAID is enabled) high incoming bandwidth ensures IP cameras can be connected</p> <p>2 HDMI (different source) and 2 VGA (different source) interfaces</p> <p>16 HDD can be used for continuous video recording</p> <p>Supports some specialist cameras, including people counting camera/ANPR (automatic number plate recognition) camera/fisheye camera</p> <p>Advanced streaming technology enables smooth live view in poor network conditions</p> <p>Supports RAID 0, 1, 5, 6, 10 and N+1 hot spare for even more reliable data storage, effectively avoids data loss risks</p>	تماس بگیریید	

209	BRACKET			
210	DS-1671ZJ-SD11	In-Ceiling Mount for 4-inch PTZ Camera Steel & Plastic Hikvision White	IRR 9,370,000	
211	DS-1604ZJ	Wall mounting bracket with the junction box Aluminum alloy material with surface spray treatment Junction box supports bottom outlet and back outlet The hook for safety rope facilitates speed dome's installation	IRR 38,180,000	